# **TRB142**

INDUSTRIAL RUGGED LTE RS232 GATEWAY



# CONNECTIVITY

4G/LTE (Cat 1), 3G, 2G

# **SERIAL PORT**

Equipped with RS232 for serial communication

# **COMPACTNESS**

Small size, easy installation

# **DURABILITY**

Rugged aluminum housing

## 9-30V

Wide range of supported power supply voltages

## RMS

Compatible with Teltonika Remote Management System

**TRB142** 

#### PRODUCT DESCRIPTION

// TRB142 comes with a widely used RS232 interface for remote device management.

// It is equipped with mission-critical LTE Cat 1 capabilities and software based on OpenWRT, hence offering a high degree of customization.


// Just like the other TRB series products, it provides a wide range of software features such as SMS control, VPN, IPsec, Firewall, and FOTA support.

// This gateway is durable, offers a wide range of power supply voltages, and is compatible with Teltonika Networks Remote Management System (RMS).



FRONT VIEW

**BACK VIEW** 



Mobile antenna connector

\*\*REMOVE PANIL TO RESERTS M \*\*

USB MOBILE RESET

USB connector Reset button

# **KEY FEATURES**

## **HARDWARE**

| Mobile                 | 4G/LTE (Cat 1), 3G, 2G   |
|------------------------|--|
| CPU                    | Qualcomm, ARM Cortex A7, 1.2 GHz   |
| Memory                 | 512 MBytes Flash (70 MBytes for userspace), 128 MBytes RAM (50 MBytes for userspace) |
| Powering option        | 4pin power socket, 9-30 VDC  |
| SIM                    | 1 x Internal SIM holder (2FF)  |
| Antenna connectors     | 1 x SMA for mobile   |
| Intputs/Outputs        | On 4pin socket: 2 x Digital input/Digital open collector output (configurable)       |
| Serial                 | 1 x RS232  |
| Other                  | 1 x Micro USB slave  |
| Status LEDs            | 3 x Connection type, 5 x Signal strength, 1 x Power                                  |
| Operating temperature  | -40° C to 75° C  |
| Housing                | Aluminium housing with DIN rail mounting option                                      |
| Dimensions (W x H x D) | 75 x 25 x 65 mm  |
| Weight                 | 135 g  |

### **SOFTWARE**

| Operating system          | RutOS  |
|---------------------------|--|
| Network protocols         | TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, DHCP, Telnet |
| Monitoring and Management | WEB UI, CLI, SSH, SMS, TR-069, SNMP, JSON-RPC, MQTT, RMS   |
| Connection monitoring     | Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection                          |
| Cloud solutions           | RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx                            |
| Modbus                    | TCP slave, TCP master, RTU master, RTU gateway, Modbus over MQTT                                     |
| Serial                    | Console, Over IP, Modem, NTRIP, Modbus   |

RMS

